

# YANTON®

PROFESSIONAL FM TRANSCEIVER

# GT-03

TRI-BAND FM TRANSCEIVER

TRI BAND  
DUAL DISPLAY  
DUAL STANDBY



## Tri-color backlit selectable

2×128 GROUPS CHANNELS STORAGE  
LED FLASH LIGHT  
VOICE COMPANDER  
SCRAMBLER FUNCTION  
PTT & ANI ID  
DTMF ENCODER & DECODER

# YANTON® GT-03



## Tri-color backlit selectable

2×128 GROUPS CHANNELS STORAGE  
LED FLASH LIGHT  
VOICE COMPANDER  
SCRAMBLER FUNCTION  
PTT & ANI ID  
DTMF ENCODER & DECODER



TRI BAND / DUAL DISPLAY / DUAL STANDBY

## SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	136-174MHz, 350-390MHz	RF Power	1W/5W
	400-480MHz	Modulate Mode	F3E
Operating Temperature	-20°C~+60°C	Max. Freq. Deviation	≤5KHz
Frequency Combination	Phase lock frequency synthesize	Remain Wave Radiation	<-60dB
Frequency Stability	±2.5ppm	Transmitting Current	≤1000mA
Memory Channel	2*128 Channels	RECEIVE PART	
Working voltage	DC7.4V (Li-ion Battery)	Sensitivity	<0.20μV(12dB SINAD)
Antenna Impedance	50Ω	Squelch Sensitivity	<0.20μV
Operating Mode	Simplex of co-frequency or alien	Intermodulation Antijamming	50dB
	frequency	Audio Power output	500mW
Dimension	115mm×62mm×32mm	Receiving Current	≤100mA
Weight	130g (Include Battery Pack)	Squelch Standby	20mA

**Notice:** Saving your presence, no additional notice will be sent if specification changes because of technology-improving.